Canon
imageANYWARE

REALiS SX7 Mark II

PRODUCT NAME	REALiS SX7 Mark II
ITEM CODE	4233B002
UPC CODE	013803119404

Suggested List Price:

$6,999.99

FEATURES

- **Native SXGA+ Resolution (1400 x 1050) -** *Supports wide screen computer displays*
- **LCOS Technology** *- High image quality and reliability*
- **AISYS Optical Engine -** *Efficiently handles light, producing superior image quality*
- **4000 Lumens -** *Bright, crisp images*
- **1.7x Powered Zoom Lens -** *Genuine Canon Optics*
- **Short Throw Distance -** *Project a 100" screen from only 9.8 feet away*
- **Photo Image Mode -** *Make precise adjustments to ensure optimum color accuracy*
- **Adobe RGB and sRGB -** *Exceptional color matching of photographic images*
- **Advanced Color Management System -** *6-axis color adjustment*
- **Auto Setup -** *Automatic input signal and keystone correction*
- **Guidance Functions -** *On screen help provides easy, step-by-step operation*
- **Off and Go -** *Internal fan makes it possible to unplug the projector and go*
- **Warranty -** *3 Year Parts and Labor / 120 Day on Lamp*
- **Canon's Triple P (Projector Protection Program) -** *A service program that provides a loaner projector of equal or greater quality to the end user in the event their projector needs to be repaired**

** Based on avaliability, for complete details contact your Canon sales representative*

CONTENTS OF KIT

- **REALiS SX7 Mark II Projector**
- **Power Cable**
- **DVI-VGA Computer Cable**
- **Component Video Cable**
- **Lens Cap**
- **Remote Control (with AAA batteries)**
- **Soft Carrying Case**
- **Warranty Card**

OPTIONAL ACCESSORIES

ITEM CODE NO.	DESCRIPTION	SUGGESTED LIST PRICE
2396B001	RS-LP04 REPLACEMENT LAMP	579.00
3095B001	RS-CL07 CEILING MOUNT	999.00
3096B001	RS-CL08 CEILING EXTENSION : (16" - 24")	379.00
3097B001	RS-CL09 CEILING EXTENSION : (24" - 39")	399.00
7502A001	LV-CA29 DVI-D CABLE	69.00
0610B001	RS-CA01 RS-232C CABLE (9.8")	60.00
1025V632	RS-232C CONTROL CABLE (18")	10.00
1261V591	T-WC070 WIDE CONVERTER LENS	1,499.00
1332V132	REALIS PROJECTOR CASE	269.00

PACKAGING INFORMATION

PROJECTOR	H x W x D	WEIGHT
REALiS SX7 Mark II	15.4 x 19.8 x 10.7 in (392 x 502 x 272 mm)	19.2 lbs (8.7 kg)

SPECIFICATIONS

BASIC	IMAGING DEVICE		0.7" Reflective LCD Panels (LCOS x 3)
	ASPECT RATIO		4:3
	NATIVE RESOLUTION		SXGA+ (1400 x 1050)
	BRIGHTNESS		4000 Lumens
	UNIFORMITY		88%
	CONTRAST		1000:1
	KEYSTONE	VERTICAL	+/- 20 degrees (Auto/Manual)
		HORIZONTAL	+/- 20 degrees (Manual)
OPTICS	PROJECTION LENS		F1.85 - 2.5, f=21.7 - 35.8mm
	LENS OFFSET		9:1, Fixed
	ZOOM		1.7x Powered, 12x Digital zoom
	FOCUS		Powered
	SCREEN SIZE		40" - 300"
	PROJECTION DISTANCE COVERAGE		3.9 - 29.5 ft (1.2 - 9.m) 100": 9.8 - 16.1 ft. (3.0 - 4.9m)
	THROW RATIO		1.46 - 2.43:1
IMAGE ADJUSTMENTS	IMAGE MODES		Standard, Presentation, Movie, Photo, Adobe RGB, sRGB
	COLOR ADJUST		Dynamic Gamma, 6-Axis (RGBCMY) Color Adjustment
	WALL CORRECTION		Auto / Manual
	IMAGE FLIP		None / Ceiling Mounted / Rear / Rear, Ceiling Mounted
	TILT ANGLE		Adjusting foot up to 10 degrees
INPUT SIGNALS	DIGITAL PC INPUT		SXGA+ / SXGA / WXGA / XGA / SVGA / VGA
	SCANNING FREQUENCY		H:15~100 kHz, V:50~100 Hz
	ANALOG PC INPUT		UXGA / SXGA+ / SXGA / WXGA / XGA / SVGA / VGA
	SCANNING FREQUENCY		H:15~100 kHz, V:50~100 Hz
	DOT CLOCK		170MHz or less
	VIDEO INPUT		NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
	COMPONENT INPUT		1080i / 1035i / 720p / 576p / 576i / 480p / 480i
	DIGITAL VIDEO INPUT		1080i / 1035i / 720p / 576p / 480p
TERMINALS	INPUT	DVI-I 29PIN	Digital PC input / Analog PC input / Digital Video input
		D-SUB 15PIN	Analog PC Input x 2
		RCA	Composite Video Input
		STEREO MINI-JACK	Stereo Audio Input x 3
	OUTPUT	D-SUB 15PIN	Analog PC output
		STEREO MINI-JACK	Stereo Audio Output x 1
	CONTROL	RS-232	D-sub 9pin
	BUILT-IN SPEAKER		1W (Mono)
LAMP	TYPE		275W NSH (AC)
	LAMP LIFE (NORMAL/QUIET)		2000 / 3000 Hours
REMOTE CONTROL	SENSOR		Wireless Infrared, Front/Back
	MOUSE CONTROL		Mouse Control Receiver (USB)
RATINGS	FAN NOISE (NORMAL/QUIET)		35/31 dB
	POWER	CONSUMPTION (NORMAL/QUIET/STANDBY)	360W / 290W / 7W
		VOLTAGE	AC100 to 240V, 50/60Hz
	TEMPERATURE	OPERATING	41° to 95° F (5° to 35° C)
		STORAGE	-22° to 104° F (-30° to 60° C), 5%RH ~ 90%RH
	DIMENSIONS (W x D x H)		10.5" x 13.2" x 4.5" (226mm x 336mm x 114mm)
	WEIGHT		10.6 lbs (4.8 kg)

** All prices, specifications, and availabilities subject to change without prior notice.*

Canon is a registered trademark of Canon Inc. IMAGEANYWARE is a trademark of Canon.

Effective: Mar. 8, 2010